



Geoscanners AB®



RX501

The RX501 receiver is a specially designed plug-in receiver for antennas compatible with GSSI SIR® ground penetrating systems. The receiver is for bi-static use only and that means one must have a separate transmitter to be able to make the measurements.

With many improvements in the design of the electronics and high reliability the RX501 fills a void in the industry of ground penetrating radar and gives the customer the flexibility of bi-static measurements.

Electrical Specifications:

Low Voltage Power Consumption	0.480 W
RX Aperture Time	520 ps
RX RF Bandwidth	962 Mhz
RX RF Dynamic Range	56.53 dB
RX Noise Figure	11.2 dB


Note 1: All values are measured at 50 kHz PRF with a 300 Ohms load and with no averaging.

Mechanical Specifications:

Dimensions (LxWxH) mm/inch	230x133x82 (mm) / 9.0x5.2x3.2 (inch)
Weight kg/Lbs	0.3 kg / 0.66 Lbs
Ingress Protection Rating	IP51

Environmental Specifications:

Maximum Temperature °C / °F	+40 °C / +104 °F
Minimum Temperature °C / °F	-10 °C / +14 °F
Maximum Humidity (non condensing)	96% RH
RoHS compliant	YES



Operating Instructions:

1. Insert the plug-in electronics RX501 into the antenna slot. Pay attention that the letters on the antenna and on the TR501 must be facing the same direction.
2. Secure with two bolts the plug-in electronics inserting them through the slots (1) and fastening them to the threads in the antenna case.
3. Attach the radar control cable to the plug-in electronics connector (3).
4. Connect the coaxial cable to drive the external transmitter to the connector labeled "XMIT" (5).
5. Connect the other end of the coaxial cable to the connector on the transmitter plug-in electronics.
6. Make sure that the receiver and the transmitter in the second antenna are firmly attached to the antennas before starting operating the units or powering the radar unit.
7. If survey wheel encoder operation is desired then connect a GSSI compatible survey wheel cable to the connector (2) in the front panel of the RX501. If you have any doubts whether or not your survey wheel encoder is compatible with GSSI hardware please contact us before attaching it to the unit.
8. A marker button can be attached to the marker connector (4) in the front panel.
9. Please pay attention to the fact that very high power transmitters might required external supporting units in order to work at higher PRF. If your unit is having trouble starting up check the PRF and the scan rate setting in your radar unit.

Turn on the radar and proceed with the survey.

Terms of use:

Geoscanners AB has made all reasonable efforts to ensure that all information provided through this document is accurate at the time of inclusion; however, there may be inadvertent and occasional errors for which Geoscanners AB apologizes.

Geoscanners AB accepts no liability for any inaccuracies or omissions in this document and any decisions based on information contained in this document are the sole responsibility of the reader. Geoscanners AB accepts no liability for any direct, special, indirect, or consequential damages, or any other damages of whatsoever kind, resulting from whatever cause through the use of any information obtained either directly or indirectly from this document.

This document may not be copied, reproduced, re-published, downloaded, posted, broadcast or transmitted in any way except for your own personal use. Any other use requires the prior written permission of Geoscanners AB. You agree not to adapt, alter or create a derivative work from any of the material contained in this document or use it for any other purpose other than for your personal use. You agree to use this document only for lawful purposes, and in a manner which does not infringe the rights of, or restrict or inhibit the use and enjoyment of this document by any third party.

This document and the information, names, images, pictures, logos and icons regarding or relating to Geoscanners AB, its products and services (or to third party products and services), is provided "AS IS" and on an "IS AVAILABLE" basis without any representation or endorsement made and without warranty of any kind whether express or implied, including but not limited to the implied warranties of satisfactory quality, fitness for a particular purpose, non-infringement, compatibility, security and accuracy.

In no event will Geoscanners AB be liable for any damages including, without limitation, indirect or consequential damages, or any damages whatsoever arising from use or loss of use, data, or profits, whether in action of contract, negligence or other tortious action, arising out of or in connection with the use of this document. Geoscanners AB does not warrant that the functions contained in the material contained in this document will be uninterrupted or error free, that defects will be corrected.

The names, images and logos identifying Geoscanners AB and their products and services are proprietary marks of Geoscanners AB. Nothing contained herein shall be construed as conferring by implication or otherwise any license or right under any trade mark or patent of Geoscanners AB, or any other third party.

If there is any conflict between these Terms and Conditions and rules and/or specific terms of use appearing in this document relating to specific material then the latter shall prevail.

If any of these Terms and Conditions should be determined to be illegal, invalid or otherwise unenforceable by reason of the laws of any state or country in which these Terms and Conditions are intended to be effective, then to the extent and within the jurisdiction which that Term or Condition is illegal, invalid or unenforceable, it shall be severed and deleted from this clause and the remaining terms and conditions shall survive, remain in full force and effect and continue to be binding and enforceable.

These Terms and Conditions shall be governed by and construed in accordance with the laws of Sweden. Disputes arising here from shall be exclusively subject to the jurisdiction of the courts of Sweden.

If these Terms and Conditions are not accepted in full, the use of this document must be terminated immediately.